

PRODUCT PHOTOGRAPH



GENERAL INFORMATION

| | |
|-------------------------|------------------|
| Product Code | 9680148 |
| Product Category | Lighting Systems |
| Product Family | Glow |
| Mounting Location | Ceiling |
| Application Environment | Indoor |

DIMENSION & WEIGHT

| | |
|--------------|----------------------|
| LxWxH (cm) | :200 W:2.16 H:2.7 cm |
| Cut out (cm) | N/A |
| Weight (Kgr) | N/A |

TECHNICAL DRAWING



MATERIAL & COLOR

| | |
|----------------|-----------|
| Product Color | Black |
| Body Material | Aluminium |
| Cover Material | N/A |

APPLICATION & MOUNTING

| | |
|----------------------------|--------------|
| Ambient Working Temp. | 45 C |
| Type of Protection | IP20 |
| Protection Class IK | IK08 |
| Dimmable | No |
| Type of Dimming (Optional) | N/A |
| Mounting type | Surface |
| Mounting Depth (cm) | Ceiling/Wall |
| Led Module Replaceable | N/A |
| Light Source | N/A |
| Adjustable | N/A |

COMPATIBLE WITH

— On/Off Driver: N/A

— Triac Driver: N/A

— Dali Driver: N/A



ELECTRICAL DATA

| | |
|-------------------------|----------------|
| Power (Nominal) | N/A |
| Input voltage (Nominal) | 24Vdc |
| Mains Frequency | 50/60Hz |
| Output voltage | N/A |
| Output Current | N/A |
| Power Factor | N/A |
| Efficiency | N/A |
| SVM | N/A |
| Pst | N/A |
| Class | N/A |

PHOTOMETRICAL DATA

| | |
|---------------------------|--------------|
| Luminous Flux | N/A |
| Luminous Efficacy | N/A |
| Color Temperature | N/A |
| Light Color (Designation) | N/A |
| CRI | N/A |
| SDCM | <3 |
| Beam Angle | N/A |
| UGR | N/A |

LIFESPAN

| | |
|----------|-----|
| Lifetime | N/A |
|----------|-----|

CERTIFICATES

| | |
|--------------|-----|
| Certificates | N/A |
|--------------|-----|

WARRANTY

| | |
|----------|----------------|
| Warranty | 3 Years |
|----------|----------------|

LIGHT DISTRIBUTION

