

# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH




### GENERAL INFORMATION

Product Code	9844200
Product Category	Faade & Accent Lighting
Product Family	Dusty
Mounting Location	Ground
Application Environment	Outdoor

### DIMENSION & WEIGHT

LxWxH (cm)	L:10 W:10 H:10.3 cm
Cut out (cm)	N/A
Weight (Kgr)	N/A

### TECHNICAL DRAWING



### MATERIAL & COLOR

Product Color	Silver
Body Material	Stainless Steel 316
Cover Material	N/A

### APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP67
Protection Class IK	IK10
Dimmable	N/A
Type of Dimming (Optional)	N/A
Mounting type	Surface
Mounting Depth (cm)	Ground
Led Module Replaceable	No
Light Source	Led
Adjustable	Yes

### COMPATIBLE WITH

— On/Off Driver: N/A

— Triac Driver: N/A

— Dali Driver: N/A

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

Power (Nominal)	<b>4</b>
Input voltage (Nominal)	<b>220-240Vac</b>
Mains Frequency	<b>50/60Hz</b>
Output voltage	<b>N/A</b>
Output Current	<b>N/A</b>
Power Factor	<b>N/A</b>
Efficiency	<b>N/A</b>
SVM	<b>N/A</b>
Pst	<b>N/A</b>
Class	<b>I</b>

### PHOTOMETRICAL DATA

Luminous Flux	<b>345</b>
Luminous Efficacy	<b>86.3</b>
Color Temperature	<b>3000</b>
Light Color (Designation)	<b>Warm White</b>
CRI	<b>N/A</b>
SDCM	<b>&lt;3</b>
Beam Angle	<b>30</b>
UGR	<b>N/A</b>

### LIFESPAN

Lifetime	<b>50000</b>
----------	--------------

### CERTIFICATES

Certificates	<b>CE, UKCA</b>
--------------	-----------------

### WARRANTY

Warranty	<b>5 Years</b>
----------	----------------

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

