

# NOVA LUCE


## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH



### TECHNICAL DRAWING



### COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: 9844002(Remote)

— Dali Driver: 9621523

### GENERAL INFORMATION

|                         |                   |
|-------------------------|-------------------|
| Product Code            | 9844085           |
| Product Category        | Downlights-Linear |
| Product Family          | Canon             |
| Mounting Location       | Ceiling           |
| Application Environment | Indoor            |

### DIMENSION & WEIGHT

|              |              |
|--------------|--------------|
| LxWxH (cm)   | L:11 W:3 H:4 |
| Cut out (cm) | 10,5 X 2,5   |
| Weight (Kgr) | N/A          |

### MATERIAL & COLOR

|                |           |
|----------------|-----------|
| Product Color  | Black     |
| Body Material  | Aluminium |
| Cover Material | N/A       |

### APPLICATION & MOUNTING

|                            |            |
|----------------------------|------------|
| Ambient Working Temp.      | 45 C       |
| Type of Protection         | IP20       |
| Protection Class IK        | IK04       |
| Dimmable                   | Yes        |
| Type of Dimming (Optional) | Triac/Dali |
| Mounting type              | Recessed   |
| Mounting Depth (cm)        | Ceiling    |
| Led Module Replaceable     | No         |
| Light Source               | Led        |
| Adjustable                 | No         |

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |                   |
|-------------------------|-------------------|
| Power (Nominal)         | <b>11</b>         |
| Input voltage (Nominal) | <b>220-240Vac</b> |
| Mains Frequency         | <b>50/60Hz</b>    |
| Output voltage          | <b>15Vdc</b>      |
| Output Current          | <b>600mA</b>      |
| Power Factor            | <b>&gt;0.82</b>   |
| Efficiency              | <b>ò78%</b>       |
| SVM                     | <b>ò0.4</b>       |
| Pst                     | <b>ò1</b>         |
| Class                   | <b>II</b>         |

### PHOTOMETRICAL DATA

|                           |                   |
|---------------------------|-------------------|
| Luminous Flux             | <b>541</b>        |
| Luminous Efficacy         | <b>49.2</b>       |
| Color Temperature         | <b>3000</b>       |
| Light Color (Designation) | <b>Warm White</b> |
| CRI                       | <b>&gt;90</b>     |
| SDCM                      | <b>&lt;3</b>      |
| Beam Angle                | <b>28</b>         |
| UGR                       | <b>&lt;19</b>     |

### LIFESPAN

|          |              |
|----------|--------------|
| Lifetime | <b>50000</b> |
|----------|--------------|

### CERTIFICATES

|              |                 |
|--------------|-----------------|
| Certificates | <b>CE, UKCA</b> |
|--------------|-----------------|

### WARRANTY

|          |                |
|----------|----------------|
| Warranty | <b>5 Years</b> |
|----------|----------------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

