

NOVA LUCE

PRODUCT DATASHEET

Version: 001

PRODUCT PHOTOGRAPH




GENERAL INFORMATION

Product Code	9070142
Product Category	Downlights-Linear
Product Family	Akira
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	L: 7.5 W: 4.5 H: 4.9
Cut out (cm)	6.8X3.7
Weight (Kgr)	N/A

TECHNICAL DRAWING



MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK03
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: 9844002

— Dali Driver: 9621523

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com



ELECTRICAL DATA

Power (Nominal)	5
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	7Vdc
Output Current	700mA
Power Factor	0,5
Efficiency	>73%
SVM	<0.4
Pst	<1
Class	II

PHOTOMETRICAL DATA

Luminous Flux	368
Luminous Efficacy	73.6
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	>80
SDCM	<3
Beam Angle	30
UGR	<19

LIFESPAN

Lifetime	50000
----------	--------------

CERTIFICATES

Certificates	CE, UKCA
--------------	-----------------

WARRANTY

Warranty	5 Years
----------	----------------

LIGHT DISTRIBUTION

