

# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH



### TECHNICAL DRAWING

### COMPATIBLE WITH

— On/Off Driver: N/A

— Triac Driver: N/A

— Dali Driver: N/A

### GENERAL INFORMATION

|                         |                     |
|-------------------------|---------------------|
| Product Code            | 9840109             |
| Product Category        | CV Drivers          |
| Product Family          | On Off Driver 24Vdc |
| Mounting Location       | N/A                 |
| Application Environment | Outdoor             |

### DIMENSION & WEIGHT

|              |     |
|--------------|-----|
| LxWxH (cm)   | N/A |
| Cut out (cm) | N/A |
| Weight (Kgr) | N/A |

### MATERIAL & COLOR

|                |     |
|----------------|-----|
| Product Color  | N/A |
| Body Material  | N/A |
| Cover Material | N/A |

### APPLICATION & MOUNTING

|                            |      |
|----------------------------|------|
| Ambient Working Temp.      | 45 C |
| Type of Protection         | IP67 |
| Protection Class IK        | N/A  |
| Dimmable                   | N/A  |
| Type of Dimming (Optional) | N/A  |
| Mounting type              | N/A  |
| Mounting Depth (cm)        | N/A  |
| Led Module Replaceable     | N/A  |
| Light Source               | N/A  |
| Adjustable                 | N/A  |

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



## ELECTRICAL DATA

|                         |                   |
|-------------------------|-------------------|
| Power (Nominal)         | <b>200</b>        |
| Input voltage (Nominal) | <b>200-277Vac</b> |
| Mains Frequency         | <b>50/60Hz</b>    |
| Output voltage          | <b>24Vdc</b>      |
| Output Current          | <b>N/A</b>        |
| Power Factor            | <b>N/A</b>        |
| Efficiency              | <b>N/A</b>        |
| SVM                     | <b>N/A</b>        |
| Pst                     | <b>N/A</b>        |
| Class                   | <b>N/A</b>        |

## PHOTOMETRICAL DATA

|                           |              |
|---------------------------|--------------|
| Luminous Flux             | <b>N/A</b>   |
| Luminous Efficacy         | <b>N/A</b>   |
| Color Temperature         | <b>N/A</b>   |
| Light Color (Designation) | <b>N/A</b>   |
| CRI                       | <b>N/A</b>   |
| SDCM                      | <b>&lt;3</b> |
| Beam Angle                | <b>N/A</b>   |
| UGR                       | <b>N/A</b>   |

## LIFESPAN

|          |            |
|----------|------------|
| Lifetime | <b>N/A</b> |
|----------|------------|

## CERTIFICATES

|              |                 |
|--------------|-----------------|
| Certificates | <b>CE, UKCA</b> |
|--------------|-----------------|

## WARRANTY

|          |                |
|----------|----------------|
| Warranty | <b>5 Years</b> |
|----------|----------------|

## LIGHT DISTRIBUTION

