

# NOVA LUCE

PRODUCT DATASHEET

Version: 001

## PRODUCT PHOTOGRAPH




## GENERAL INFORMATION

Product Code	<b>62002</b>
Product Category	<b>Ceiling-Gu10</b>
Product Family	<b>Universal</b>
Mounting Location	<b>Ceiling</b>
Application Environment	<b>Indoor</b>

## DIMENSION & WEIGHT

LxWxH (cm)	<b>D: 10 H: 9 cm</b>
Cut out (cm)	<b>9,3</b>
Weight (Kgr)	<b>N/A</b>

## TECHNICAL DRAWING



## MATERIAL & COLOR

Product Color	<b>White</b>
Body Material	<b>Aluminium</b>
Cover Material	<b>N/A</b>

## APPLICATION & MOUNTING

Ambient Working Temp.	<b>45 C</b>
Type of Protection	<b>IP20</b>
Protection Class IK	<b>IK03</b>
Dimmable	<b>Yes</b>
Type of Dimming (Optional)	<b>Dali</b>
Mounting type	<b>Recessed</b>
Mounting Depth (cm)	<b>Ceiling</b>
Led Module Replaceable	<b>No</b>
Light Source	<b>Led</b>
Adjustable	<b>Yes</b>

## COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: N/A

— Dali Driver: 9621523

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

Power (Nominal)	<b>13</b>
Input voltage (Nominal)	<b>220-240Vac</b>
Mains Frequency	<b>50/60Hz</b>
Output voltage	<b>N/A</b>
Output Current	<b>N/A</b>
Power Factor	<b>N/A</b>
Efficiency	<b>N/A</b>
SVM	<b>N/A</b>
Pst	<b>N/A</b>
Class	<b>II</b>

### PHOTOMETRICAL DATA

Luminous Flux	<b>1151</b>
Luminous Efficacy	<b>88.5</b>
Color Temperature	<b>3000</b>
Light Color (Designation)	<b>Warm White</b>
CRI	<b>&gt;90</b>
SDCM	<b>&lt;3</b>
Beam Angle	<b>38</b>
UGR	<b>&lt;19</b>

### LIFESPAN

Lifetime	<b>50000</b>
----------	--------------

### CERTIFICATES

Certificates	<b>CE, UKCA</b>
--------------	-----------------

### WARRANTY

Warranty	<b>5 Years</b>
----------	----------------

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

