

# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH




### GENERAL INFORMATION

Product Code	9540314
Product Category	Ceiling-Led
Product Family	Binary
Mounting Location	Ceiling/Wall
Application Environment	Indoor

### DIMENSION & WEIGHT

LxWxH (cm)	D:42.2 H:5.8 cm
Cut out (cm)	N/A
Weight (Kgr)	2,2

### TECHNICAL DRAWING



### MATERIAL & COLOR

Product Color	White & Gold
Body Material	Aluminium
Cover Material	N/A

### APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP44
Protection Class IK	IK04
Dimmable	No
Type of Dimming (Optional)	N/A
Mounting type	Surface
Mounting Depth (cm)	Ceiling/Wall
Led Module Replaceable	No
Light Source	Led
Adjustable	No

### COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: N/A

— Dali Driver: N/A

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



## ELECTRICAL DATA

Power (Nominal)	<b>30</b>
Input voltage (Nominal)	<b>220-240Vac</b>
Mains Frequency	<b>50/60Hz</b>
Output voltage	<b>40Vdc</b>
Output Current	<b>380mA</b>
Power Factor	<b>0,9</b>
Efficiency	<b>ò85%</b>
SVM	<b>?0.4</b>
Pst	<b>?1</b>
Class	<b>II</b>

## PHOTOMETRICAL DATA

Luminus Flux	<b>2690</b>
Luminous Efficacy	<b>89.7</b>
Color Temperature	<b>2700/3000/4000</b>
Light Color (Designation)	<b>Dip-Switch</b>
CRI	<b>&gt;80</b>
SDCM	<b>&lt;3</b>
Beam Angle	<b>120</b>
UGR	<b>N/A</b>

## LIFESPAN

Lifetime	<b>50000</b>
----------	--------------

## CERTIFICATES

Certificates	<b>CE ROHS</b>
--------------	----------------

## WARRANTY

Warranty	<b>5 Years</b>
----------	----------------

## LIGHT DISTRIBUTION

