

NOVA LUCE

PRODUCT DATASHEET

Version: 001

PRODUCT PHOTOGRAPH




GENERAL INFORMATION

Product Code	9040116
Product Category	Downlights-Linear
Product Family	Brandy
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	L:6.4 W:2.8 H:3.8
Cut out (cm)	6?2,4
Weight (Kgr)	N/A

TECHNICAL DRAWING



MATERIAL & COLOR

Product Color	White & Black
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK03
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: 9621520(Remote)

— Dali Driver: 9844145

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	5
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	9Vdc
Output Current	500
Power Factor	0,9
Efficiency	ò80%
SVM	60.4
Pst	ó1
Class	II

PHOTOMETRICAL DATA

Luminus Flux	420
Luminous Efficacy	84
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	>90
SDCM	<3
Beam Angle	28
UGR	<19

LIFESPAN

Lifetime	50000
----------	--------------

CERTIFICATES

Certificates	CE, UKCA
--------------	-----------------

WARRANTY

Warranty	5 Years
----------	----------------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

